



		Tires		Clutch settings		Front shocks		Engine	
Date/Track	GLARC	Front shore	left 32 / right 32	Shoe / Bell	Std /	Piston	1.3-1 hole	Type	OS R2101
Driver	Tim Long	Rear shore	left 35 / right 35	Bell clearance (mm)	0.5	Oil	700	Plug/Fuel	Plug / Fuel
Temp. °C.	air / track	Front φ	left 67 / right 67	Spring/adj. Nut(mm)	/	Spring	White	Pipe/Manifold	Pipe / Manifold
		Rear φ	left 74 / right 74	Bell axial play (mm)	0.1-0.2				
Track layout/traction	technical <input type="radio"/> low <input type="radio"/>	Body		Gearing		Piston	1.2 -2 hole	Gear ratio chart	
	mixed <input type="radio"/> medium <input checked="" type="radio"/>	Type	PF 909	1st gear	16 / 50	Oil	800	1st	48 1st 49 50 45 2nd 46 47
	fast <input type="radio"/> high <input type="radio"/>	Wing position (mm)	8	2n gear	20 / 46	Spring	Grey	1st	16 7,2 7,35 7,5 17 6,776 6.918 7,059 19 20 21
								2nd	5,684 5,811 5,937 5,4 5,52 5,64 5,143 5,257 5,371

