


Name: MIKE SWAUGER
Date: _____
Track: Rams _____

Track Conditions
Size: Open Med. Tight
Traction: High Med. Low
Surface: Smooth Med. Bumpy


Front suspension

Track width 254 mm
Ride height 5 mm
Camber angle 1.5 °
Caster angle 1 mm
Toe angle 1 out °
Rebound stop 1 mm
Bump stop
 None Use


Anti-roll bar 

Front shocks


Piston 1.1x2
Oil # 600
Spring WHITE



Rebound stop



Caster Angle



Shock position




Steering Ackerman (H0364)

A B C


Rear suspension

Track width 263 mm
Ride height 6 mm
Camber angle -3 °
Toe angle 1.5 °
Rebound stop 8 mm
Bump stop
 None Use


Anti-roll bar Wire _____ mm Adjustable 

Lower arm position
 5.5mm(A-C) 6.5mm(B-D)


H0180 Position 1.5 mm



Rebound stop



H0180 Position



Rear shocks

Piston Stock
Oil # 600
Spring Red

Shock position





Engine Type RX21 RACE WC JP
Gasket 0.6 mm Muffler 086 with Jp header
Plug C8Tf Fuel Mugen Seiki Racing Fuel
Reducer 9

Clutch Clutch shoes Black Gray
Centrifugal shoe 4mm
Spring Jp
Clutch bell clearance 0.5 mm
Spring Adj. Nut position 8.4 mm

Tire Front Type Fast 35S Rear Type Fast 35S
Dia.(start) L 67 /R 67 Dia.(start) L 74 /R 74
Dia.(finish) L _____ /R _____ Dia.(finish) L _____ /R _____

Brake pad
 Black Yellow

Body Type MS Lola WC
Body position Back mm  Rear spoile 7 mm

Drive ratio Gear ratio
 1st 16 / 49 Pully A (25 or 26) 25T 26T
2nd 20 / 45

Result
Race time / Lap _____
Best lap (1Lap) _____

Comments:
.....
.....
.....